

Product Details

- This transformer features a high-quality stainless steel case and includes multiple taps to accommodate voltagedrops. Available in 150, 300, and 600 watts, these transformers can support any project size.
- The enclosure is made of prime SS 304 grade stainless steel (a carbon steel enclosure with powder coating can be provided upon request).
- A circuit breaker is included for circuit protection.
- Block terminals provide an easy way for customers to connect the secondary windings.
- A photocell and timer can be connected according to customer requirements.

Technical Details

- Frequency- 50/60 Hz
- Insulation class – F, H
- Max. regulation – 10%
- Dielectric – 2000v, primary to secondary for 1 second.
- Dielectric – 2000v, all windings to lamination for 1 second.

Features

- Made in accordance with UL 1838 standard
- Secondary circuit breaker
- Two knockout sizes for conduit
- Removable bottom & 4ft Grounded plug
- Terminal block for easy access

LANDSCAPE LIGHTING TRANSFORMER

SPECIFICATIONS	150W	300W	600W
Finish	Stainless Steel	Stainless Steel	Stainless Steel
Photocell/Timer	Compatible	Compatible	Compatible
Secondary Circuit Breaker	Orange	White	Circuit #1 & Circuit #2, White
Multi Tap	12V, 13V, 14V, 15V	12V, 13V, 14V, 15V	12V, 14V, 16V, 18V, 20V, 22V
Dimensions (in.)	10.55 x 5.7 x 5.1	16.57 X 6.61 X 5.9	16.57 X 6.61 X 6
Dimmable	On Primary Side	On Primary Side	On Primary Side



Miracle Electronic Devices Pvt. Ltd.

No. 48/1, Karihobanahalli Village,
Thigalarapalya Main Road,
Peenya 2nd Stage,
Bengaluru - 560058,
Karnataka, India.

+ (91)-(80)-28362750 | + (91)-(80)-28362751

+ (91)-(80)-28362752

info@miracle.net.in | sales@miracle.net.in