



Product Details

- This transformer features a high-quality stainless steel case and includes multiple taps to accommodate voltagedrops. Available in 150, 300, and 600 watts, these transformers can support any project size.
- The enclosure is made of prime SS 304 grade stainless steel (a carbon steel enclosure with powder coating can be provided upon request).
- A circuit breaker is included for circuit protection.
- Block terminals provide an easy way for customers to connect the secondary tappings.
- A photocell and timer can be connected according to customer requirements.

Technical Details

- Frequency- 50/60 Hz
- Insulation class F, H
- Max. regulation 10%
- Dielectric 2000v, primary to secondary for 1 second.
- Dielectric 2000v, all windings to lamination for 1 second.

Features

- UL 1838 Certified
- Secondary circuit breaker
- Two knockout sizes for conduit
- Removable bottom & 4ft Grounded plug
- Terminal block for easy access

LANDSCAPE LIGHTING TRANSFORMER

SPECIFICATIONS 150W 300W 600W **Finish Stainless Steel** Stainless Steel Stainless Steel **Photocell/Timer** Compatible Compatible Compatible **Secondary Circuit Breaker** White Circuit #1 & Circuit #2. White Orange **Multi Tap** 12V, 13V, 14V, 15V 12V, 13V, 14V, 15V 12V, 14V, 16V, 18V, 20V, 22V **Dimensions (in.)** 10.55 x 5.7 x 5.1 16.57 X 6.61 X 5.9 16.57 X 6.61 X 6 **Dimmable On Primary Side On Primary Side On Primary Side**



Miracle Electronic Devices Pvt. Ltd.

No. 48/1, Karihobanahalli Village, Thigalarapalya Main Road, Peenya 2nd Stage Bengaluru - 560058, Karnataka, India.







+(91)-(80)-28362752



info@miracle.net.in | sales@miracle.net.in